








Metal enclosures surface mounting MCB Distribution Board - Type A

-  Total safety
-  Complete
-  Time-saving features
-  High quality
-  Great design

Applications



Marking



Performance

Incomer ratings	(A) 100 (main switch) 80 (RCD)
RCD sensitivity	(mA) 30
Rated voltage	(V) 240
Busbar rating	(A) 100
Busbar short-circuit capacity	(kA) 16
Terminal capacity	(mm ²) 50 (main switch/RCD) (mm ²) 25 (E+N terminal bars)
Enclosure colour	Light grey (RAL7035)
Ingress protection	IP40

Features

- In accordance with BS5486 and BS EN 60439-3
- Sturdy folded sheet steel construction
- Durable structured powder coated finish
- Matching light grey used throughout range
- Phase busbar rating 120A
- Incoming device cable terminal capacity 50mm²
- Terminal bar cable capacity 25mm²
- Shrouded neutral terminal bar
- Generous wiring room even using 1 module RCBO
- Comprehensive range of incomers
- Pre assembled ready to accept MCBs and RCBOs
- DIN enclosure option so you can "design it yourself"



Modular 200 - Type A - MCB Distribution Board

	No of outgoing ways	H x W x D (mm) (code)	Terminal Capacity	Ref. No.	Pack.
Main Switch – 2P 100A	6	270x368x127 (A)	50mm ²	617971	1
	9	270x412x127 (B)	50mm ²	617972	1
	13	270x484x127 (C)	50mm ²	617973	1
RCD – 2P 80A 30mA	6	270x368x127 (A)	50mm ²	619974	1
	9	270x412x127 (B)	50mm ²	619975	1
	13	270x484x127 (C)	50mm ²	619976	1
Split Load – 2P 100A Main Switch, 2P 80A 30mA RCD	10	270x412x127 (B)	50mm ²	619977	1
	10	270x412x127 (B)	50mm ²	619978	1
	14	270x484x127 (C)	50mm ²	619979	1
DIN Enclosure	10	270x368x127 (A)	-	617957	1
	14	270x412x127 (B)	-	617958	1
	18	270x484x127 (C)	-	617959	1

Accessories

	Clean earth kit	
	617960	1

Modular 200 Type A

A

B

C

D

E

F

G

X

