



## Insulated enclosures Surface mounting

**Abaco S**

**IP40**

### Marking

**CE**

### Standards

EN/IEC 695-2-1, CEI 670, CEI 23-48

### Applications



The Abaco surface enclosures are used for power distribution in house building and commercial buildings as offices, banks, etc.

### Features

- Protection degree IP40.
- Total insulation: class II ☐ .
- Four dimensions in two colours.
- Colours: grey RAL 7030 and white RAL 9010.
- Range from 8 modules up to 39 modules.
- Flame resistance: self extinguishing material, resists the 650°C.
- Operating temperature: -15°C to +60°C.
- Chemical resistance against water, salt solution, acid rain.
- Surface mounting with flat panels; easy mounting of cable entries.
- The DIN rails can be taken off to make the equipment externally.
- The position of the mounting frame can be adjusted.

**Abaco S - Transparent door**



Colour	H x W x D (mm)	Modules 17.5 mm	Number of rows	Ref. No.	Pack.
Grey: RAL 7030	230 x 200 x 110	8/10	1	<b>619375</b>	14
White: RAL 9010	230 x 200 x 110	8/10	1	<b>619376</b>	14
Grey: RAL 7030	300 x 200 x 110	12/14	1	<b>619369</b>	10
White: RAL 9010	300 x 200 x 110	12/14	1	<b>619372</b>	10
Grey: RAL 7030	315 x 400 x 110	24/26	2	<b>619370</b>	1
White: RAL 9010	315 x 400 x 110	24/26	2	<b>619373</b>	1
Grey: RAL 7030	315 x 525 x 110	36/39	3	<b>619371</b>	1
White: RAL 9010	315 x 525 x 110	36/39	3	<b>619374</b>	1

**Accessories**

<b>Insulated support for earth and neutral</b>  for enclosure 6/10 modules connection range 2 x 16 mm <sup>2</sup> + 8 x 10 mm <sup>2</sup>	<b>619319</b>	120	
	<b>619320</b>	120	
	<b>619321</b>	60	
	for enclosure 24/36 modules connection range 2 x 16 mm <sup>2</sup> + 12 x 10 mm <sup>2</sup>		
<b>Blank plate</b>  Grey, 5 modules  White, 5 modules  Metallised black, 5 modules	<b>619323</b>	150	
	<b>619338</b>	150	
	<b>619339</b>	1	
	for enclosure 10/14 modules connection range 2 x 16 mm <sup>2</sup> + 12 x 10 mm <sup>2</sup>		
<b>Security lock</b>  24 and 36 modules	<b>619350</b>	1	

Abaco S

A

B

C

D

E

F

G

X

