



Waterproof enclosures Surface mounting

Aquaria

IP65

Approval / Marking



Standards

EN 60439-1, IEC 695-2-1,
CEI 23-48, CEI 23-49

Applications



Aquaria is the best choice for power distribution purposes in premises with a need for high protection degree eg. power plants, technical areas small laboratories, etc..

Features

- Total insulation
- Protection degree IP65 - IK08
- Colour: RAL 7035
- Transparent lid or hinged door (3 rows)
- For DIN-rail equipment up to 92.5 mm
- DIN-rails adjustable up to 3 different levels
- Operating temperature: -5°C to +60°C
- Flame resistance: resist the 650°C
- Non UV stable
- Enclosures can not be coupled

Power dissipation

Enclosure	# mod.	Ref. No.	Maximal power dissipation (W)
1 row	5	597956	8
1 row	8	597957	11
1 row	12	597958	17
1 row	12	597959	20
2 rows	24	597960	30
3 rows	48	597961	45

New



Aquaria - Waterproof enclosures surface mounting IP65



Colour	Dimensions mm (H x L x W)	Modules 17,5mm	# rows	Art. No.	ENCLOSURE		EARTH BAR	
					Ref. No.	Pack	Ref. No.	Pack
Gray RAL 7035	120 x 160 x 90	3/5	1	AQA005PG	597956	1/40/840	597962	1/20/120
Gray RAL 7035	200 x 160 x 90	4/8	1	AQA008PG	597957	1/26/546	597963	1/20/120
Gray RAL 7035	225 x 200 x 110	6/12	1	AQA012PG	597958	1/14/294	619320	1/20/120
Gray RAL 7035	250 x 250 x 145	6/12	1	AQA912PG	597959	1/1/152	619320	1/20/120
Gray RAL 7035	375 x 250 x 145	24	2	AQA024PG	597960	1/1/108	619320	1/20/120
Gray RAL 7035	550 x 350 x 145	48	3	AQA048PG	597961	1/1/44	619321	1/10/60

Accessories - Earth bars⁽¹⁾

Connection	# earth bars	Ref. No.	Pack
2 x 16 mm ² + 5 x 10 mm ²	1	597962	1/20/120
2 x 16 mm ² + 8 x 10 mm ²	2	597963	1/20/120
2 x 16 mm ² + 12 x 10 mm ²	2	619320	1/20/120
2 x 16 mm ² + 12 x 10 mm ²	4	619321	1/10/60

(1) To be ordered separately



New