



- Complete customized units for maximum operator comfort in all areas of production
- In design and execution coordinated system
- Ingress protection IP 65
- Integrated handles
- Compact size
- Service friendly construction

### Included in delivery:

Standard execution with steel workplate, front door, rear door, plinth, locking system, 2 fix shelves.  
Customized execution according demand

## Technical Data

### Operating enclosure:

Aluminium profile Commander system with individual sizes, configurations and colours

### Coupling system:

Customized execution, turnable, optionally inclinable with huge cable outlet. Optionally with tube or direct mounting

### Base cabinet:

Sheet steel base cabinet with front door and rear door, individual internal execution with shelves and removable shelf  
Dimensions (W x H x D): 600 x 1100 x 600 mm  
Door with 180° opening area hinged right, lockable

### Colour:

RAL 7035 / RAL 7043  
other colours on request

### Ingress protection:

IP 65

Customized execution on demand

---

# Industrial Workstation RIW

---

## Construction

### Commander



### Coupling unit



### Base cabinet



## Base cabinet

Standard execution

Order No. **38.03 01 01**



Work plate



Front door, rear door



Plinth



Locking system



2 fix shelves

# Industrial Workstation RIW

## Base cabinet individual execution

Custom made solution acc. specification

Order No. **38.03 99 99 8**



Front door, rear door



Front door, rear wall screwed



Base:  
Plinth, 100 mm height  
4 steerable rolls



Front door with window, rear door



Front door with window, rear wall screwed



Locking systems:  
Triangular  
Square  
Double ward  
Lock cylinder

## Accessories



Connection diagramm pocket A4 mounted on door



Connection diagramm pocket A3 mounted on door



Fix shelf



Removable shelf



Rack mounting



Flange plate with seal membrane



Interior lamp with door switch



Multiple socket outlet



Filter fan / outlet filter

# Industrial Workstation RIW

## Coupling



Execution 1: GTK electronic

	Order No.
Foot stand	<b>49.45 72 00</b>
Connecting tube, variable length	<b>49.45 10 00*</b>
Coupling	<b>49.45 73 00</b>

\* please specify individual length



Execution 2: GT 48/2

	Order No.
Foot stand	<b>49.49 72 00</b>
Connecting tube, variable length	<b>10.09 41 58*</b>
Flange coupling	<b>49.49 77 00</b>

\* please specify individual length



Execution 2: GTN II

	Order No.
Foot stand	<b>49.47 72 00</b>
Connecting tube, variable length	<b>49.47 10 99*</b>
Coupling	<b>49.47 73 00</b>

\* please specify individual length



Execution 4: GTN II - Foot stand

	Order No.
Foot stand turnable with adapter plate	<b>49.47 72 20</b>
Foot stand turnable	<b>49.47 72 21</b>



Execution 5: Moterm - Inclining adapter

	Order No.
Inclining adjustment	<b>50.02 01 01</b>



Execution 6: Inclining adapter

	Order No.
Inclining adapter GTN II	<b>49.47 80 00</b>
Inclining adapter GT 48/2 and GTK electronic	<b>49.49 80 00</b>

Company \_\_\_\_\_  
 Contact \_\_\_\_\_  
 Address \_\_\_\_\_

Telephone \_\_\_\_\_  
 Fax \_\_\_\_\_  
 E-Mail \_\_\_\_\_

**Base cabinet**

Standard execution  Custom made execution

**Colour**

Standard: center part RAL 7035, side stripes / work plate RAL 7043  
 Individual colours (please fill in)

center part: RAL \_\_\_\_\_ side stripes: RAL \_\_\_\_\_ work plate: RAL \_\_\_\_\_

**Door**

front door, rear door  front door, rear wall screwed  
 front door with window, rear door  front door with window, rear wall screwed

**Base**

plinth, 100 mm high  4 steerable rolls

**Locking system**

Triangular lock  Double ward  
 Square lock  lock cylinder with key  
 other \_\_\_\_\_

**Accessories**


connection diagramm pocket A4  connection diagramm pocket A3  
 fix shelf  removable shelf  
 rack mounting  flange plate with seal membrane  
 interior lamp with door switch  
 filter fan  outlet filter

quantity \_\_\_\_\_

side C  side D

quantity \_\_\_\_\_

side C  side D



**Commander systems**

ComTronic  SL 2000  SL 3000  SL 4000

**Coupling**

GTK electronic: foot stand, tube, coupling tube length \_\_\_\_\_ mm  
 GT 48/2: foot stand, tube, flange coupling tube length \_\_\_\_\_ mm  
 GTN II: foot stand, tube, coupling tube length \_\_\_\_\_ mm  
 GTN II: foot stand turnable  
 GTN II: foot stand turnable with adapter plate  
 inclining adjustment Moterm  
 inclining adapter GTN II  
 inclining adapter GT 48/2 and GTK electronic

---

# Industrial Workstation RIW

---

## Applications

