



- Halogen-free duroplastic
- Glow-wire test as per VDE 0471 up to 960°C
- Cable cross-sections of 2.5² to 25²
- Suitable for use in locations that are subject to fire hazards as per VDE 0100 Part 482



Junction boxes WK

WK 007

80 x 80 x 38 mm



Description

Order no.

Junction box acc. to DIN EN 60670 (VDE 0606), Duroplastic, halogen-free, with IP54 attachment bushes, with blanking plug M16, seal range 6 - 10 mm

IP54

2,5²

IK05

400V
AC**WK 007-L**

Grey, without terminal



402 907 01

WK 007-2,5²Grey, with screw terminal 5-pole - 2.5 mm², (6 x 1.5² / 4 x 2.5²)

402 407 01

WK 040

87 x 87 x 45 mm



Junction box acc. to DIN EN 60670 (VDE 0606), U_i=690V, Duroplastic, halogen-free, with IP54 attachment bushes, with blanking plug M20, seal range 8 - 13.5 mm

IP54

4²

IK05

690V
AC**WK 040-L**

Grey, without terminal

404 907 01

WK 040-S

Grey, without terminals



455 907 01

WK 040-4²Grey, with screw terminal 5-pole - 4 mm², (6 x 2.5² / 4 x 4²)

404 407 01

WK 060

100 x 100 x 50 mm



Description

Order no.

Junction box acc. to DIN EN 60670 (VDE 0606), $U_i=690V$, Duroplastic, halogen-free, with IP54 attachment bushes, with blanking plug M25, seal range 9 - 18.5 mm

IP54

6²

IK05



690V
AC



WK 060-L

Grey, without terminal

406 906 01



WK 060-6²

Grey, with 5-pole screw terminal - 6 mm², (5 x 4² / 4 x 6²)

406 406 01

WK 100

115 x 115 x 66 mm



Junction box acc. to DIN EN 60670 (VDE 0606), $U_i=690V$, Duroplastic, halogen-free, with IP54 attachment bushes, with blanking plug M32, seal range 13 - 23 mm, with sealing kit

IP54

10²

IK05



690V
AC



WK 100-L

Grey, without terminal

410 906 01

WK 100-10²

Grey, with 5-pole screw terminal - 10 mm², (5 x 4² / 4 x 6² / 3 x 10²)

410 406 01

