



▲ External mounting brackets for quick installation

- Fuse-protected branch with maintained function
- Clamping area up to 35²
- Especially sturdy
- Ideal for time and material savings in building installation planning
- State-tested by the MPA NRW
- Current test certificate available online at www.spelsberg.com
- Extensive range of accessories such as rawlplugs and cable glands for all junction boxes
- The right solution for every cross-section and application

IP66

E30

FE180

F400

35²

IK08



450V
AC/DC



Junction boxes WKE 200 - 4

abn

«Эйбэн»

Тел./факс +375(17) 390-51-85


Тел. +375(44) 592-00-86

info@abn.by

www.abn.by

WKE 202 RK

115 x 115 x 93 mm



Description

Order no.

Cable junction and connection box with IP66 certified acc. EN 60670, with electrical functional integrity E30 acc. to DIN 4102 Part 12, with insulation integrity FE180 acc. IEC 60331-11 as well as functional class F400 acc. EN 12101, enclosure and terminal strips made from halogen-free special duroplastic

IP66

E30

FE180

F400

6²



WKE 202 RK

862 202 01


Junction box 5-pole, termination capability per pole 2 x 0.5 - 6 mm²,

Accessories supplied:

Wall plug set ø 6 mm, 2 cable glands M32,
seal range 17 - 26 mm

WKE 203 RK

115 x 115 x 93 mm



Cable junction and connection box with IP66 certified acc. EN 60670, with electrical functional integrity E30 acc. to DIN 4102 Part 12, with insulation integrity FE180 acc. IEC 60331-11 as well as functional class F400 acc. EN 12101, Enclosure and terminal strips made from halogen-free special duroplastic

IP66

E30

FE180

F400

4²



WKE 203 RK

862 203 01


Junction box 3-pole, termination capability for each pole 4 x 0.5 - 4 mm²,

Accessories supplied:

Wall plug set ø 6 mm, 3 cable glands M25,
seal range 6 - 15 mm

WKE 204 RK

115 x 115 x 93 mm



Description

Order no.

Cable junction and connection box with IP66 certified acc. EN 60670, with electrical functional integrity E30 acc. to DIN 4102 Part 12, with insulation integrity FE180 acc. IEC 60331-11 as well as functional class F400 acc. EN 12101, Enclosure and terminal strips made from halogen-free special duroplastic

IP66

E30

FE180

F400

4²



450V
AC/DC



WKE 204 RK

862 204 01


Junction box with fused E30 branch, 3-pole in transition area, termination capability for each pole 4 x 0.5 - 4 mm², 3-pole in fused E30 branch, Termination capability for each pole 1 x 0.5 - 4 mm², Fuse (20 x 5 mm) max. 6.3A

Accessories supplied:

Wall plug set ø 6 mm, 3 cable glands M25, seal range 6 - 15 mm

WKE 302 RK

160 x 160 x 110 mm



Cable junction and connection box with IP66 certified acc. EN 60670, with electrical functional integrity E30 acc. to DIN 4102 Part 12, with insulation integrity FE180 acc. IEC 60331-11 as well as functional class F400 acc. EN 12101, Enclosure and terminal strips made from halogen-free special duroplastic

IP66

E30

FE180

F400

16²



450V
AC/DC



WKE 302 RK

862 302 01


Junction box 5-pole, termination capability for each pole 4 x 4 - 16 mm²

Accessories supplied:

Wall plug set ø 6 mm, 2 cable glands M40, seal range 17 - 27 mm

WKE 303 RK

160 x 160 x 110 mm



Description

Order no.

Cable junction and connection box with IP66 certified acc. EN 60670, with electrical functional integrity E30 acc. to DIN 4102 Part 12, with insulation integrity FE180 acc. IEC 60331-11 as well as functional class F400 acc. EN 12101, enclosure and terminal strips made from halogen-free special duroplastic

IP66

E30

FE180

F400

10°



WKE 303 RK

862 303 01


Junction box 5-pole, termination capability for each pole 4 x 2.5 - 10 mm²

Accessories supplied:

Wall plug set ø 6 mm, 3 cable glands M32, seal range 17 - 26 mm

WKE 304 RK

160 x 160 x 110 mm



Cable junction and connection box with IP66 certified acc. EN 60670, with electrical functional integrity E30 acc. to DIN 4102 Part 12, with insulation integrity FE180 acc. IEC 60331-11 as well as functional class F400 acc. EN 12101, enclosure and terminal strips made from halogen-free special duroplastic

IP66

E30

FE180

F400

10°



WKE 304 RK

862 304 01


Junction box with fused E30 branch, 5-pole in transition area, termination capability for each pole 2 x 2.5 - 10 mm², 3-pole in fused E30 branch, Termination capability for each pole 1 x 1.5 - 10 mm², Fuse (20 x to 5 mm) max. 6.3A

Accessories supplied:

Wall plug set ø 6 mm, 2 cable glands M40, seal range 17 - 27 mm, 1 cable gland M25, seal range 6 - 15 mm

WKE 402 RK

200 x 200 x 110 mm



Description

Order no.

Cable junction and connection box with IP66 certified acc. EN 60670, with electrical functional integrity E30 acc. to DIN 4102 Part 12, with insulation integrity FE180 acc. IEC 60331-11 as well as functional class F400 acc. EN 12101, enclosure and terminal strips made from halogen-free special duroplastic

IP66

E30

FE180

F400

35²



450V
AC/DC



WKE 402 RK

862 402 01


Junction box 5-pole, termination capability for each pole 2 x 2.5 - 35 mm²

Accessories supplied:

Wall plug set ø 6 mm, 2 cable glands M50, seal range 23 - 34 mm

WKE 403 RK

200 x 200 x 110 mm



Cable junction and connection box with IP66 certified acc. EN 60670, with electrical functional integrity E30 acc. to DIN 4102 Part 12, with insulation integrity FE180 acc. IEC 60331-11 as well as functional class F400 acc. EN 12101, enclosure and terminal strips made from halogen-free special duroplastic

IP66

E30

FE180

F400

16²



450V
AC/DC



WKE 403 RK

862 403 01


Junction box 5-pole, termination capability for each pole 4 x 4 - 16 mm²

Accessories supplied:

Wall plug set ø 6 mm, 2 cable glands M40, seal range 17 - 27 mm,
1 cable gland M32, seal range 17 - 26 mm

WKE 404 RK

200 x 200 x 110 mm



Description

Cable junction and connection box with IP66 certified acc. EN 60670, with electrical functional integrity E30 acc. to DIN 4102 Part 12, with insulation integrity FE180 acc. IEC 60331-11 as well as functional class F400 acc. EN 12101, enclosure and terminal strips made from halogen-free special duroplastic

Order no.



WKE 404 RK

862 404 01

Junction box with fused E30 branch, 5-pole in transition area, Termination capability for each pole 2 x 2.5 - 35 mm², 3-pole in fused E30 branch, termination capability for each pole 1 x 1.5 - 10 mm², Fuse (20 x 5 mm) max. 6.3A

Accessories supplied:

Wall plug set ø 6 mm, 2 cable glands M50, seal range 23 - 34 mm, 1 cable gland M32, seal range 17 - 26 mm

WKE 405 LSA

200 x 200 x 110 mm



Tested system: WKE 405 - cable junction boxes with time-saving (solder, screw and stripping free) connection technology for cables with functional integrity according to DIN 4102 Part 12 - tested by the MPA Dresden




WKE 405 LSA

862 405 01

Junction box equipped with two LSA-Plus connector blocks, respectively for 10 double wires (2 x 10 DA), the LSA-Plus contacts are suitable for a solid conductor with 0.4 to 0.8 mm diameter and an outside insulation diameter of 0.7 to 1.6 mm

Accessories supplied:

Wall plug set ø 6 mm, 4 cable glands M25, seal range 9 - 19 mm



External fixing lugs



External fastening kit V2A

WKE 200 ABL

860 400 01

External fastening kit V2A, for WKE 200 up to WKE 400, Material stainless steel V2A (1.4301), Set = 4 pcs.

KVS

890 040 01

Cable gland protection set, is needed for IK 09 when cable glands are used, for WKE 200 up to WKE 400, IK09, Material stainless steel V2A (1.4301), Set = 3 pcs.